

Сглобка на главната връзка MAW POWERTEX (широка)

Информация за продукта



The POWERTEX Master Link assembly MAW (Wide) is part of the range of Powertex G10 Lifting Sling Chain Components. The MAW assembly features wider toplinks and sublinks, making it ideal for larger hooks and steel wire rope slings with thimble eyes. It serves as the top assembly for both three-leg and four-legged chain sling or steel wire rope sling assemblies.

Available for 6 mm up to 16 mm chain and from WLL 3t up to WLL 21.2t. All models are welded.

Powerdex G10 Range benefits:

- 25% higher capacity compared to traditional Grade 8 components
- All POWERTEX G10 components are painted in luminous red
- Multi-functional master links and components are included in the range to allow quick and cost-effective assembly of chain slings
- The components meet EN 1677 part 1/2/3/4 +25% WLL
- Each forged component is crack detection tested, and samples are proof load tested.
- Each component is type tested in the factory and fatigue rated to 20,000 cycles at 1.5 times the WLL
- Full traceability through a batch number
- Replacement spare parts available
- All components are chromium 6 free
- POWERTEX 2.2 certificate enclosed with each box of components
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling needs to be rated as Grade 8 in accordance with EN 818-2 ... [Read more](#)

Маркировка: Съгласно релевантния стандарт, POWERTEX + модел (MAW-6-10) + код за проследимост.

Работна температура: -40°C до +200°C без намаляване на WLL

Покритие: Прахово боядисани в светлочервено

Стандарт: EN 1677-4 (+25% WLL) , AS 3776


Забележка: Всички модели са заварени

Коефициент на безопасност: 4:1

Клас : 10

Сглобка на главната връзка MAW POWERTEX (широка)

Чертеж



Технически данни

Продуктов номер	Код	WLL тон	Работна дължина мм	За верига 3-4 рамена мм	A мм	B мм	D мм	a мм	b мм	d мм	H мм	S мм	Тегло кг
402100300780	MAW-6-10	3	270	6	150	90	19	120	70	14	28	7	1,8
402100530780	MAW-8-10	5,3	300	8	160	95	22	140	80	18	28	8	3
402100840780	MAW-10-10	8,4	360	10	200	120	30	160	95	22	43	11	6,5
402101410780	MAW-13-10	14,1	440	13	250	150	40	190	110	26	43	13	12,8
402102100780	MAW-16-10	21,2	500	16	300	200	50	200	120	32	60	17	23