

Веригова блокчица POWERTEX Blackline PCB-S2.

Информация за продукта



POWERTEX

Chain Block POWERTEX Blackline PCB-S2 is a hoist of high quality which is durable and easy to operate using the ergonomic hand chain. The hoist is powder coated in matt black, and mounted with a black chain, which makes it perfect for use on stages and in the amusement industry.

The hoist is in a compact, lightweight construction.

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- Fine calibrated European made COROLIM® protected load chain for smooth operation
- The unique surface treatment gives excellent corrosion protection and quiet run
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

Option:

... [Read more](#)

Материал: Здрава стоманена конструкция.

Маркировка: Съгласно релевантния стандарт, CE - маркировка, POWERTEX, Модел, Работна товароносимост (WLL), Верига, Сериен номер, Ръководство на потребителя / QR код.

Работна температура: От -10°C до +50°C.


Покритие: Прахово боядисан корпус в матово черно и оцинковани рамкови компоненти.

Стандарт: EN 13157, EN 818-7

Коефициент на безопасност: 4:1

Веригова блокчица POWERTEX Blackline PCB-S2.

Чертеж



Технически данни

Продуктов номер	WLL тон	A мм	B мм	C мм	D мм	E мм	H min мм	ø мм мм
16.10PCBS20050000BK	0,5	128	75	130	35	22	280	20
16.10PCBS20100000BK	1	142	76	150	40	26	330	25