



General use



Стоманени въжета ROPETEX S49

Информация за продукта

ROPETEX



ROPETEX S49 is a wire rope for general purposes like hanging signs, control and signaling devices, but not for lifting. It's most used in small diameters up to 6 mm. ROPETEX S49 is equipped with a Steel Core (WSC).

ROPETEX S42 is the same rope but has a Fibre Core (FC) and is therefore more flexible.

Структура: 6x7-WSC (7x7)

Маркировка: Съгласно релевантния стандарт

Работна температура: -40°C до +200°C, за работни температури между 100°C и 200°C намалете MBF с минус 10 %.

Стандарт: EN 12385-4

Предупреждение: Да не се използва за повдигане

Коефициент на запълване: 0,55

Продуктов номер	Диаметър на въжето мм	Tensile strength N/mm ²	Покритие	Rope lay	Мин. разкъсващо усилие kN	Метална зона мм ²	Lubrication	Тегло кг/100м
101100104270040	1	1 960	Galvanized	sZ	0,76	0,43	Dry	0,38
101100154270040	1,5	1 960	Galvanized	sZ	1,71	0,97	Dry	0,86
101100204270040	2	1 960	Galvanized	sZ	3,04	1,73	Dry	1,54
101100244270040	2,4	1 960	Galvanized	sZ	4,38	-	Dry	2,2
101100254270040	2,5	1 960	Galvanized	sZ	4,75	2,7	Dry	2,4
101100304270040	3	1 960	Galvanized	sZ	6,84	3,89	Dry	3,46
101100404270040	4	1 960	Galvanized	sZ	12,2	6,91	Dry	6,14
101100604270040	6	1 960	Galvanized	sZ	27,4	15,6	Dry	14