

Ръчен верижен талреж КИТО АТЕХ среден

Информация за продукта



Manual chain Hoist ATEX Medium from KITO

- Equipment classification Gas II 2G EX h IIB T3 Gb (zone 1)
- Equipment classification Dust II 2D EX h IIIB T200°C Db (zone 21) • Impact resistant housing
- Double pawl spring
- Highly accurate and durable gear mechanism
- Double brake enclosure keeping out rainwater and dust
- Mechanical load brake
- Low pulling force on the hand chain
- Overload protection by slipping clutch

Exposure Protected: Equipment is executed with non-sparking materials for fast mechanical contact parts for hand chain movements and internal fast moving hoist parts, extended with unique and reliable bronze coated load hooks. ... [Read more](#)

Маркировка: Съгласно релевантния стандарт, CE - маркировка


Работна температура: -40°C до +40°C

Покритие: Прашково покритие

Стандарт: EN 13157

Ръчен верижен талреж КИТО АТЕХ среден

Чертеж



Технически данни

Код	WLL тон	Височина на повдигане м	Number of falls	Headroom mm	Верига мм	A мм	B мм	D мм	E мм	F мм	F1 мм	Тегло кг
K010	1	3	1	295	6,3	91	71	99	62	34,6	29	11,5
K020	2	3	1	375	8	95	87	125	77	40	36	20