Lifting Solutions Group
Axel Johnson International

Chain Block POWERTEX Blackline PCB-S2 without chain

Product information



Chain Block POWERTEX Blackline PCB-S2 is a hoist of high quality which is durable and easy to operate using the ergonomic hand chain. The hoist is powder coated in matt black, and mounted with a black chain, which makes it perfect for use on stages and in the amusement industry.
The hoist is in a compact, lightweight construction.

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- Fine calibrated European made COROLIM® protected load chain for smooth operation
- The unique surface treatment gives excellent corrosion protection and quiet run
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

Option:

... *Read more*

Material: Durable all steel construction
Marking: According to standard, CE-mark, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code
Temperature range: -10°C up to +50°C
Finish: Powder coated body in matt black and plated frame components
Standard: EN 13157, EN 818-7


Safety factor: 4:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Block POWERTEX Blackline PCB-S2 without chain

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	H min mm	ø mm mm
16.10PCBS20050000BK	0.5	128	75	130	35	22	280	20
16.10PCBS20100000BK	1	142	76	150	40	26	330	25

© November 2026 - All Rights Reserved