

## Chain Block POWERTEX Blackline PCB-S2 without chain

### Product information



### POWERTEX

Chain Block POWERTEX Blackline PCB-S2 is a hoist of high quality which is durable and easy to operate using the ergonomic hand chain. The hoist is powder coated in matt black, and mounted with a black chain, which makes it perfect for use on stages and in the amusement industry.

The hoist is in a compact, lightweight construction.

#### Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- Fine calibrated European made COROLIM® protected load chain for smooth operation
- The unique surface treatment gives excellent corrosion protection and quiet run
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

#### Option:

Hand chain

[... Read more](#)

**Material:** Durable all steel construction

**Marking:** According to standard, CE-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

**Temperature range:** -10°C up to +50°C


**Finish:** Powder coated body in matt black and plated frame components

**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1

## Chain Block POWERTEX Blackline PCB-S2 without chain

### Blueprint



### Technical data

| Part code           | WLL ton | A mm | B mm | C mm | D mm | E mm | H min mm | ø mm mm |
|---------------------|---------|------|------|------|------|------|----------|---------|
| 16.10PCBS20050000BK | 0.5     | 128  | 75   | 130  | 35   | 22   | 280      | 20      |
| 16.10PCBS20100000BK | 1       | 142  | 76   | 150  | 40   | 26   | 330      | 25      |