



Web Lashing Powertex Trailer

Product information

POWERTEX



Powertex Trailer web lashings are available as endless or 2-part lashings and used for professional haulers.

These web lashings are flexible and durable, made of high strength polyester yarn and steel ratchets and hooks.

Suitable for professional transporters with high standard tensioning force STF and high LC.

- Light and flexible with LC 2000 daN and STF 350 daN
- Orange webbing with 5 black stripes for easy identification
- Both long part and short part carry blue identification labels
- Tag give information on STF and Lashing Capacity for different lashing connections
- Each part is marked with a unique serial number for safe equipment registration
- The blue information label is protected by additional layer of transparent plastic for long life
- Year/Month calendar printed on the label where next inspection date can be marked or punched
- All lashings carry a white label with important warning instructions and user instruction pictogram
- Each lashing marked with QR code to access full user manual
- Cr6 free galvanization – better for health and environment
- Trailer can be supplied with other lengths and other end fittings on request.

Safety factor: Webbing min. 3, rachets min. 2 and hooks min. 2.

Material: Polyester and steel

Marking: According to standard, Powertex, LC, STF, length, manufacturing year, batch number, serial number, QR code, inspection calendar, user warning instructions

Temperature range: -40°C up to +120°C

Standard: EN 12195-2

Note: Protect the lashings from sharp edges

Part code	LC daN	2xLC (daN)	Length m	Band width mm	Design	Fitting	STF daN	Colour	Weight kg
14.01TRA01ZZ100OE	2,000	4,000	10	50	Endless	-	350	Orange	1.96
14.02TRA01WD0555OE	2,000	4,000	6	50	2-part	Wire hook double	350	Orange	2.06
14.02TRA01WD0595OE	2,000	4,000	10	50	2-part	Wire hook double	350	Orange	2.48
14.03TRA01WD005OE	2,000	-	0.5	50	Short part-1	Wire hook double	350	Orange	-
14.04TRA00WD095OE	2,000	-	9.5	50	Long part	Wire hook double	350	Orange	-