



Ropetex 55

Product information

ROPETEX



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope. Flexibility is optimised by the unique strand and rope construction. Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

RopeTex Ropes are lubricated with the very latest High Performance Wire rope lubricants to give excellent corrosion protection, fatigue life combined with low fling off

ISO 4309 Rope Category No: All Diameters RCN.23-1

Features: Very High Breaking Load

Material: High Carbon Steel

Marking: According to standard

Finish: Galvanised as standard

Standard: EN 12385-4

Fill factor: 0,64

RCN: 23-1

Part code	Rope diameter	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
01.G35X55080H	8	2,160	Galvanized	zZ	50.5	-	SupplierStandard	27.6
01.G35X55080G	8	1,960	Galvanized	zZ	-	-	SupplierStandard	27.6
01.G35X55090H	9	2,160	Galvanized	zZ	64	-	SupplierStandard	34.4

01.G35X55090G	9	1,960	Galvanized	zZ	-	-	SupplierStandard	34.4
01.G35X55100H	10	2,160	Galvanized	zZ	79	-	SupplierStandard	43
01.G35X55100G	10	1,960	Galvanized	zZ	-	-	SupplierStandard	43
01.G35X55110H	11	2,160	Galvanized	zZ	95.6	-	SupplierStandard	52
01.G35X55110G	11	1,960	Galvanized	zZ	-	-	SupplierStandard	52
01.G35X55120H	12	2,160	Galvanized	zZ	114	-	SupplierStandard	62
01.G35X55120G	12	1,960	Galvanized	zZ	-	-	SupplierStandard	62
01.G35X55130H	13	2,160	Galvanized	zZ	134	-	SupplierStandard	72
01.G35X55130G	13	1,960	Galvanized	zZ	-	-	SupplierStandard	72
01.G35X55140H	14	2,160	Galvanized	zZ	155	-	SupplierStandard	84
01.G35X55140G	14	1,960	Galvanized	zZ	-	-	SupplierStandard	84
01.G35X55150H	15	2,160	Galvanized	zZ	178	-	SupplierStandard	96
01.G35X55150G	15	1,960	Galvanized	zZ	-	-	SupplierStandard	96
01.G35X55160H	16	2,160	Galvanized	zZ	202	-	SupplierStandard	110
01.G35X55160G	16	1,960	Galvanized	zZ	-	-	SupplierStandard	110
01.G35X55170H	17	2,160	Galvanized	zZ	228	-	SupplierStandard	120
01.G35X55170G	17	1,960	Galvanized	zZ	-	-	SupplierStandard	120
01.G35X55180H	18	2,160	Galvanized	zZ	256	-	SupplierStandard	135
01.G35X55180G	18	1,960	Galvanized	zZ	-	-	SupplierStandard	135
01.G35X55190H	19	2,160	Galvanized	zZ	285	-	SupplierStandard	150
01.G35X55190G	19	1,960	Galvanized	zZ	-	-	SupplierStandard	150
01.G35X55200H	20	2,160	Galvanized	zZ	316	-	SupplierStandard	166
01.G35X55200G	20	1,960	Galvanized	zZ	-	-	SupplierStandard	166

01.G35X55220H	22	2,160	Galvanized	zZ	382	-	SupplierStandard	201
01.G35X55220G	22	1,960	Galvanized	zZ	-	-	SupplierStandard	201
01.G35X55240H	24	2,160	Galvanized	zZ	455	-	SupplierStandard	245
01.G35X55240G	24	1,960	Galvanized	zZ	-	-	SupplierStandard	245
01.G35X55260H	26	2,160	Galvanized	zZ	527	-	SupplierStandard	297
01.G35X55260G	26	1,960	Galvanized	zZ	-	-	SupplierStandard	297
01.G35X55280H	28	2,160	Galvanized	zZ	612	-	SupplierStandard	345
01.G35X55280G	28	1,960	Galvanized	zZ	-	-	SupplierStandard	345