Lifting Solutions Group
Axel Johnson International

Electric Chain Hoist KITO EQM with Motorized Trolley

Product information



Ultimate lightweight and compact size, meticulous and dedicated design, with integrated body protecting the high-performance and highly functional unit.

- The combination of idea and technology materialize in a lightweight size.
  - Meticulous inverter-dedicated design
- A dual-safety mechanism prevents accidents from excessive loads.
  - Equipped with a friction clutch and electronic overload limiter
- Smooth and ergonomic operation
- Shuts off motor current during excessive lifting/lowering to prevent accidents.
- Meticulous long-life design
- Suitable for severe environments and working conditions
  - Simple design with Grade M6 High-end duty rating with unique motor frame fins and fan cover
- World-class KITO original chain - Superstrong nickel-plated load chain
- Visual indication of maintenance timing
- Shuts off the motor circuit in case of emergency.
- Higher inspector work efficiency - Easier maintenance
- Environmentally friendly
- Use:
  - Lifting Up/Down, Traversing Left/Right

... *Read more*


Temperature range: -20℃ up to 40℃


© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Electric Chain Hoist KITO EQM with Motorized Trolley

Blueprint





Technical data

Code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Beam width mm	Motor kW	Traversing motor Output kW	Lifting speed m/min. High (light load) 0-30 % WLL	Lifting speed m/min. High 30-100 % WLL	C mm	D mm	b mm	d mm	e mm	e´ mm	g mm	i mm	j mm	k mm	m mm	n mm	r mm	t mm	Weight kg
EQM010IS-IS	1	3	7.1/1.2	1	58-163	1.5	0.4	9.2	7	490	565	315	220	515	179	31	95	22	130	205	109	51	31	75

© November 2026 - All Rights Reserved