

## **Manual Chain Hoist KITO CB ATEX**

## **Product information**

**General:** This chain hoist gives you safe operation in potentially explosive atmosphere. It is protected against explosive gases, vapors and dust. Hereby KITO ensures the qualified use of the KITO CB ATEX chain hoist series conforming to the ATEX Directive. Available for use in T4 temperature environments.

## Options:

- Different suspension types include: include top hook and KITO Universal Trolleys TS model ATEX version (plain or hand geared trolley configurations) for improved load control.
- Overload Protection Device (OLL): the unique slip clutch mechanism protects the hoist from damage in the event of an excessive overload without increasing the size of the unit.
- Special capacities are available on request.

Marking: Type plate with WLL, CE-marking and serial number.

Finish: Painted.

Safety factor: 4:1

Part code	WLL ton	Lifting height m	Number of falls	Туре	Load chain mm	Hand force max. kg	a mm	b mm	d mm	e mm	f mm	g mm	s mm	c mm	Weight kg
16.10CB005ESH030030	0.5	2.5	1	CB005 ATEX	6.3 x 19	29	162	161	2,500	71	99	39	42.5	295	11.5
16.10CB010ESH030030	1	2.5	1	CB010 ATEX	7.1 x 21	35	171	182	2,500	78	112	34	47.5	350	14.5
16.10CB020ESH030030	2	3	2	CB020 ATEX	7.1 x 21	33	171	235	3,100	78	162	42.5	56	510	24
16.10CB030ESH030030	3	3	2	CB030 ATEX	9.0 x 27	34	192	282	3,600	91	194	46.5	63	600	41

## Blueprint

