Lifting Solutions Group
Axel Johnson International

Push Trolley KITO HD3C Handycat

Product information



- Revolutionary stable 3 bolt system, for large beam range
- Material traceability for all load carrying parts
- Suitable for all beam types
- Easy to mount principle by turning the spindle
- Easy click in system for the hoists
- Smart securing system preventing the trolley to loose beam adjustment
- Wheel break supports, hand chain guide with anti-drop device
- Trolley wheels with lifetime lubricated bearing
- Corrosion protection: Electric galvanized body parts
- Suspension ring, high grade steel
- Also available in Explosion Protected Execution (ATEX)

... *Read more*

Marking: According to standard
Standard: EN 13157

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Push Trolley KITO HD3C Handycat

Blueprint



Technical data

WLL ton	Beam width mm	A mm	B mm	C mm	D mm	D1 mm	E mm	F mm	G mm	H mm	L mm	M mm	N mm	N1 mm	N2 mm	O mm	R mm	S mm	Weight kg
1	55-180	60	75	18	45	120	20	60	29	189	190	65	90	166-BW/2	228-BW	100	99	22	7
1	180-305	60	75	18	45	120	20	60	29	189	190	65	90	1,400	349-BW	100	99	22	8
2	74-180	80	100	22	55	150	27	75	35	197	255	65	90	171-BW/2	237-BW	100	123	25	14
2	180-305	80	100	22	55	150	27	75	35	197	255	65	90	2,200	358-BW	100	123	25	15
3.2	90-180	100	120	25	67	197	35	95	40	210	300	70	95	176-BW/2	245-BW	100	144	32	23
3.2	180-305	100	120	25	67	197	35	95	40	210	300	70	95	236-BW/2	366-BW	100	144	32	24
5	106-180	125	150	30	90	230	40	115	60	235	375	100	130	188-BW/2	259-BW	135	174	38	39
5	180-305	125	150	30	90	230	40	115	60	235	375	100	130	248-BW/2	380-BW	135	174	38	40

© November 2026 - All Rights Reserved