

Horizontal Pipe Lifting Clamp TTL

Product information



Clamp for horizontal lifting and transporting of tubes, pipes, tube bundles, rolls and other solid round materials. The clamp is locked in the open position. To perform lifting, the operator must activate the handle and hold it up while the force on the lifting eye is going upwards. When laying down the load, the clamp automatically locks itself open.

Features:

- Lightweight design and easy to use.
- Tough quality body.
- Can be delivered with protection to avoid damaging of the load.
- Higher WLL or jaw openings available upon request.

... [Read more](#)


Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening

Temperature range: -40°C to + 100°C

Standard: EN 13155

Horizontal Pipe Lifting Clamp TTL

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	Rmm mm	T mm	U min-max mm	V min-max mm	X mm mm	Ymm mm	Weight kg
16.85800550	0.5 TTL	0.5	48.3-114.3	48.3-114.3	45	300-400	146-207	47	15	4.5
16.85801011	1 TTL	1	114.3-219.1	114.3-219.1	45	430-615	110-170	47	15	9
16.85802021	2 TTL	2	219.1-368	219.1-368	64	670-955	225-320	56	16	31
16.85803036	3 TTL	3	368-508	368-508	64	875-1165	590-710	56	16	39