

Wire Rope Lifting Sling WLS-176

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(* \varnothing 3mm - \varnothing 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Master link in one end and self-locking safety hook in other end, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request..

... [Read more](#)

Wire Rope Lifting Sling WLS-176

Technical data

| Diameter mm | WLL ton |
|----------------|------------|
| 3 | 0.12 |
| 4 | 0.21 |
| 5 | 0.32 |
| 6 | 0.47 |
| 7 | 0.64 |
| 8 | 0.82 |
| 9 | 1.04 |
| 10 | 1.28 |
| 11 | 1.55 |
| 12 | 1.84 |
| 13 | 2.17 |
| 14 | 2.51 |
| 16 | 3.3 |
| 18 | 4.1 |
| 20 | 5.1 |
| 22 | 6.2 |
| 24 | 7.38 |
| 26 | 8.66 |
| 28 | 10.04 |
| 32 | 13.12 |
| 36 | 16.59 |