



## Wire Rope Lifting Sling WLS-275

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>**

**Design:** Master link in one end and eyehooks with safety latch in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
3	0.16	0.16	0.12
4	0.29	0.29	0.21
5	0.45	0.45	0.32
6	0.66	0.66	0.47
7	0.89	0.89	0.64
8	1.15	1.15	0.82
9	1.45	1.45	1.04
10	1.79	1.79	1.28

11	2.17	2.17	1.55
12	2.57	2.57	1.84
13	3.03	3.03	2.17
14	3.52	3.52	2.51
16	4.6	4.6	3.3
18	5.81	5.81	4.1
20	7.17	7.17	5.1
22	8.69	8.69	6.2
24	10.33	10.33	7.38
26	12.13	12.13	8.66
28	14.06	14.06	10.04
32	18.37	18.37	13.12
36	23.23	23.23	16.59
40	28.78	28.78	20.56
44	34.69	34.69	24.78
48	41.37	41.37	29.55
52	52.04	52.04	34.69

## Technical data