

Wire Rope Lifting Sling WLS-264

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²

Design: Master link in one end and soft eyes in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length and eye lengths with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

[... Read more](#)

Wire Rope Lifting Sling WLS-264

Technical data

Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
3	0.16	0.16	0.12
4	0.29	0.29	0.21
5	0.45	0.45	0.32
6	0.66	0.66	0.47
7	0.89	0.89	0.64
8	1.15	1.15	0.82
9	1.45	1.45	1.04
10	1.79	1.79	1.28
11	2.17	2.17	1.55
12	2.57	2.57	1.84
13	3.03	3.03	2.17
14	3.52	3.52	2.51
16	4.6	4.6	3.3
18	5.81	5.81	4.1
20	7.17	7.17	5.1
22	8.69	8.69	6.2
24	10.33	10.33	7.38
26	12.13	12.13	8.66
28	14.06	14.06	10.04
32	18.37	18.37	13.12
36	23.23	23.23	16.59
40	28.78	28.78	20.56
44	34.69	34.69	24.78
48	41.37	41.37	29.55
52	52.04	52.04	34.69