



Wire Rope Lifting Sling WLS-473

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²

Design: Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
3	0.25	0.25	0.18
4	0.44	0.44	0.31
5	0.68	0.68	0.49
6	0.98	0.98	0.7
7	1.34	1.34	0.96
8	1.72	1.72	1.23
9	2.18	2.18	1.56
10	2.69	2.69	1.92

11	3.25	3.25	2.32
12	3.85	3.85	2.75
13	4.55	4.55	3.25
14	5.28	5.28	3.77
16	6.9	6.9	4.93
18	8.71	8.71	6.22
20	10.75	10.75	7.68
22	13.03	13.03	9.31
24	15.5	15.5	11.07
26	18.19	18.19	13
28	21.08	21.08	15.06
32	27.56	27.56	19.69
36	34.84	34.84	24.89
40	43.17	43.17	30.84
44	52.04	52.04	37.17
48	62.06	62.06	44.33
52	75.85	75.85	52.04

Technical data