

## Endless webbing slings 0,5 - 10 t

### Product information



Single-layered endless webbing slings are also available with a double layer, which doubles the. Workload capacity for the same sling width.

... [Read more](#)

**Features:** RFID-ready

**Material:** 100% polyester

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C - +100 °C

**Standard:** EN 1492-1

**Note:** Color coded

**Warning:** Standard dimensional tolerance is  $\pm 3\%$ . Lengths can vary within the tolerance range!.

**Safety factor:** 7:1

## Endless webbing slings 0,5 - 10 t

### Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
UNV05XX	0.5	-	0.4	1	0.7	0.5	25	White
UNV0501	0.5	0.5	0.4	1	0.7	0.5	25	White
UNV0501.5	0.5	0.75	0.4	1	0.7	0.5	25	White
UNV0502	0.5	1	0.4	1	0.7	0.5	25	White
UNV0503	0.5	1.5	0.4	1	0.7	0.5	25	White
UNV0504	0.5	2	0.4	1	0.7	0.5	25	White
UNV0505	0.5	2.5	0.4	1	0.7	0.5	25	White
UNV0506	0.5	3	0.4	1	0.7	0.5	25	White
UNV0508	0.5	4	0.4	1	0.7	0.5	25	White
UNV0510	0.5	5	0.4	1	0.7	0.5	25	White
UNV05005	0.5	0.25	0.4	1	0.7	0.5	25	White
UNV1XX	1	-	0.8	2	1.4	1	50	Violet
UNV101	1	0.5	0.8	2	1.4	1	50	Violet
UNV102	1	1	0.8	2	1.4	1	50	Violet
UNV103	1	1.5	0.8	2	1.4	1	50	Violet
UNV104	1	2	0.8	2	1.4	1	50	Violet
UNV105	1	2.5	0.8	2	1.4	1	50	Violet
UNV106	1	3	0.8	2	1.4	1	50	Violet
UNV108	1	4	0.8	2	1.4	1	50	Violet
UNV110	1	5	0.8	2	1.4	1	50	Violet
UNV2XX	2	-	1.6	4	2.8	2	60	Green
UNV201	2	0.5	1.6	4	2.8	2	60	Green
UNV202	2	1	1.6	4	2.8	2	60	Green
UNV203	2	1.5	1.6	4	2.8	2	60	Green
UNV204	2	2	1.6	4	2.8	2	60	Green
UNV205	2	2.5	1.6	4	2.8	2	60	Green
UNV206	2	3	1.6	4	2.8	2	60	Green
UNV208	2	4	1.6	4	2.8	2	60	Green
UNV210	2	5	1.6	4	2.8	2	60	Green
UNV207	2	3.5	1.6	4	2.8	2	60	Green
UNV3XX	3	-	2.4	6	4.2	3	90	Yellow

## Endless webbing slings 0,5 - 10 t

### Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
UNV301	3	0.5	2.4	6	4.2	3	90	Yellow
UNV302	3	1	2.4	6	4.2	3	90	Yellow
UNV303	3	1.5	2.4	6	4.2	3	90	Yellow
UNV304	3	2	2.4	6	4.2	3	90	Yellow
UNV305	3	2.5	2.4	6	4.2	3	90	Yellow
UNV306	3	3	2.4	6	4.2	3	90	Yellow
UNV308	3	4	2.4	6	4.2	3	90	Yellow
UNV310	3	5	2.4	6	4.2	3	90	Yellow
UNV4XX	4	-	3.2	8	5.6	4	120	Grey
UNV402	4	1	3.2	8	5.6	4	120	Grey
UNV403	4	1.5	3.2	8	5.6	4	120	Grey
UNV404	4	2	3.2	8	5.6	4	120	Grey
UNV405	4	2.5	3.2	8	5.6	4	120	Grey
UNV406	4	3	3.2	8	5.6	4	120	Grey
UNV408	4	4	3.2	8	5.6	4	120	Grey
UNV410	4	5	3.2	8	5.6	4	120	Grey
UNV5XX	5	-	4	10	7	5	150	Red
UNV502	5	1	4	10	7	5	150	Red
UNV503	5	1.5	4	10	7	5	150	Red
UNV504	5	2	4	10	7	5	150	Red
UNV505	5	2.5	4	10	7	5	150	Red
UNV506	5	3	4	10	7	5	150	Red
UNV508	5	4	4	10	7	5	150	Red
UNV510	5	5	4	10	7	5	150	Red
UNV6XX	6	-	4.8	12	8.4	6	180	Brown
UNV602	6	1	4.8	12	8.4	6	180	Brown
UNV603	6	1.5	4.8	12	8.4	6	180	Brown
UNV604	6	2	4.8	12	8.4	6	180	Brown
UNV605	6	2.5	4.8	12	8.4	6	180	Brown
UNV606	6	3	4.8	12	8.4	6	180	Brown
UNV608	6	4	4.8	12	8.4	6	180	Brown

## Endless webbing slings 0,5 - 10 t

### Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
UNV610	6	5	4.8	12	8.4	6	180	Brown
UNV8XX	8	-	6.4	16	11.2	8	240	Blue
UNV802	8	1	6.4	16	11.2	8	240	Blue
UNV803	8	1.5	6.4	16	11.2	8	240	Blue
UNV804	8	2	6.4	16	11.2	8	240	Blue
UNV805	8	2.5	6.4	16	11.2	8	240	Blue
UNV806	8	3	6.4	16	11.2	8	240	Blue
UNV808	8	4	6.4	16	11.2	8	240	Blue
UNV810	8	5	6.4	16	11.2	8	240	Blue
UNV10XX	10	-	8	20	14	10	300	Orange
UNV1002	10	1	8	20	14	10	300	Orange
UNV1003	10	1.5	8	20	14	10	300	Orange
UNV1004	10	2	8	20	14	10	300	Orange
UNV1005	10	2.5	8	20	14	10	300	Orange
UNV1006	10	3	8	20	14	10	300	Orange
UNV1008	10	4	8	20	14	10	300	Orange
UNV1010	10	5	8	20	14	10	300	Orange