

Round slings 0,5 - 500 t

Product information



Fibre roundslings with extra strong cover for any lifting.

Note! Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Special lengths up to 30 m and roundslings with higher WLL are also available up to 500 t. Also available GB extreema slings with Dyneema fiber. Ask for more! [... Read more](#)

Features: RFID-ready

Material: 100% polyester

Marking: According to standard, CE-marked

Temperature range: -40°C-(+)100°C


Standard: EN 1492-2

Note: Color coded | Length is effective working length EWL

Safety factor: 7:1

Round slings 0,5 - 500 t

Blueprint



Technical data

Part code	WLL ton	EWL m	Packing	Colour
PAR101	1	0.5	75	Violet
PAR102	1	1	50	Violet
PAR103	1	1.5	40	Violet
PAR104	1	2	30	Violet
PAR105	1	2.5	25	Violet
PAR106	1	3	15	Violet
PAR108	1	4	15	Violet
PAR110	1	5	10	Violet
PAR112	1	6	10	Violet
PAR1XX	1	-	-	Violet
PAR201	2	0.5	60	Green
PAR202	2	1	40	Green
PAR203	2	1.5	25	Green
PAR204	2	2	20	Green
PAR205	2	2.5	15	Green
PAR206	2	3	12	Green
PAR208	2	4	8	Green
PAR210	2	5	7	Green
PAR212	2	6	6	Green
PAR2XX	2	-	-	Green
PAR301	3	0.5	40	Yellow
PAR302	3	1	30	Yellow

Round slings 0,5 - 500 t

Technical data

Part code	WLL ton	EWL m	Packing	Colour
PAR303	3	1.5	20	Yellow
PAR304	3	2	12	Yellow
PAR305	3	2.5	12	Yellow
PAR306	3	3	10	Yellow
PAR308	3	4	8	Yellow
PAR310	3	5	6	Yellow
PAR312	3	6	5	Yellow
PAR3XX	3	-	-	Yellow
PAR401	4	0.5	50	Grey
PAR402	4	1	20	Grey
PAR403	4	1.5	14	Grey
PAR404	4	2	12	Grey
PAR405	4	2.5	8	Grey
PAR406	4	3	8	Grey
PAR408	4	4	6	Grey
PAR410	4	5	5	Grey
PAR412	4	6	4	Grey
PAR4XX	4	-	-	Grey
PAR501	5	0.5	25	Red
PAR502	5	1	15	Red
PAR503	5	1.5	10	Red
PAR504	5	2	8	Red
PAR505	5	2.5	7	Red
PAR506	5	3	6	Red
PAR508	5	4	4	Red
PAR510	5	5	4	Red
PAR512	5	6	3	Red
PAR5XX	5	-	-	Red
PAR602	6	1	8	Brown
PAR603	6	1.5	8	Brown
PAR604	6	2	6	Brown

Round slings 0,5 - 500 t

Technical data

Part code	WLL ton	EWL m	Packing	Colour
PAR605	6	2.5	6	Brown
PAR606	6	3	4	Brown
PAR608	6	4	4	Brown
PAR610	6	5	3	Brown
PAR612	6	6	2	Brown
PAR6XX	6	-	-	Brown
PAR802	8	1	-	Blue
PAR803	8	1.5	-	Blue
PAR804	8	2	-	Blue
PAR805	8	2.5	-	Blue
PAR806	8	3	-	Blue
PAR808	8	4	-	Blue
PAR810	8	5	-	Blue
PAR812	8	6	-	Blue
PAR816	8	8	-	Blue
PAR820	8	10	-	Blue
PAR824	8	12	-	Blue
PAR8XX	8	-	-	Blue
PAR1002	10	1	-	Orange
PAR1003	10	1.5	-	Orange
PAR1004	10	2	-	Orange
PAR1005	10	2.5	-	Orange
PAR1006	10	3	-	Orange
PAR1008	10	4	-	Orange
PAR1010	10	5	-	Orange
PAR1012	10	6	-	Orange
PAR1016	10	8	-	Orange
PAR1020	10	10	-	Orange
PAR1024	10	12	-	Orange
PAR10XX	10	-	-	Orange
PAR1208	12	4	-	Orange

Round slings 0,5 - 500 t

Technical data

Part code	WLL ton	EWL m	Packing	Colour
PAR1210	12	5	-	Orange
PAR1212	12	6	-	Orange
PAR1502	15	1	-	Orange
PAR1503	15	1.5	-	Orange
PAR1504	15	2	-	Orange
PAR1505	15	2.5	-	Orange
PAR1506	15	3	-	Orange
PAR1508	15	4	-	Orange
PAR1510	15	5	-	Orange
PAR1512	15	6	-	Orange
PAR1516	15	8	-	Orange
PAR1520	15	10	-	Orange
PAR1524	15	12	-	Orange
PAR15XX	15	-	-	Orange
PAR2003	20	1.5	-	Orange
PAR2004	20	2	-	Orange
PAR2005	20	2.5	-	Orange
PAR2006	20	3	-	Orange
PAR2008	20	4	-	Orange
PAR2010	20	5	-	Orange
PAR2012	20	6	-	Orange
PAR2014	20	7	-	Orange
PAR2016	20	8	-	Orange
PAR2020	20	10	-	Orange
PAR2024	20	12	-	Orange
PAR20XX	20	-	-	Orange
PAR3004	30	2	-	Orange
PAR3005	30	2.5	-	Orange
PAR3006	30	3	-	Orange
PAR3008	30	4	-	Orange
PAR3010	30	5	-	Orange

Round slings 0,5 - 500 t

Technical data

Part code	WLL ton	EWL m	Packing	Colour
PAR3012	30	6	-	Orange
PAR3016	30	8	-	Orange
PAR3020	30	10	-	Orange
PAR3024	30	12	-	Orange
PAR3030	30	15	-	Orange
PAR30XX	30	-	-	Orange
PAR4005	40	2.5	-	Orange
PAR4006	40	3	-	Orange
PAR4008	40	4	-	Orange
PAR4010	40	5	-	Orange
PAR4012	40	6	-	Orange
PAR4016	40	8	-	Orange
PAR4020	40	10	-	Orange
PAR4024	40	12	-	Orange
PAR40XX	40	-	-	Orange
PAR5002	50	1	-	Orange
PAR5005	50	2.5	-	Orange
PAR5006	50	3	-	Orange
PAR5008	50	4	-	Orange
PAR5010	50	5	-	Orange
PAR5012	50	6	-	Orange
PAR5016	50	8	-	Orange
PAR5020	50	10	-	Orange
PAR5024	50	12	-	Orange
PAR50XX	50	-	-	Orange