Lifting Solutions Group
Axel Johnson International

Connection link, grade 80

Product information

Connecting link is used for connecting short link grade 80 chains to different components in a lifting sling.

... *Read more*



Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-1
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Connection link, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain Ø mm	A mm	D mm	K mm	L mm	S mm	Weight kg
LL6	1.12	42	6	15	7,5	46	61	-	0.08
LL78	2	60	7-8	19	8,5	59	77	-	0.146
LL10	3.15	68	10	25	12	69,5	96,5	-	0.3
LL13	5.3	87	13	30,5	-	90	122,5	16	0.65
LL16	8	108	16	36	19	101,5	141,5	-	1.15
LL20	12.5	121	20	42	23	119	165,5	-	2.1
LL22	15	141	22	49	24,5	152	206,5	-	2.87
LL26	21.2	158	26	58,5	31,5	162	225,5	-	4.5
LL32	31.5	205	32	67,5	38,5	194	272	-	8.21

© November 2026 - All Rights Reserved