

Master link assemblies 3-4-I, grade 80

Product information



Masterlink for 3- and 4-leg chain sling assemblies.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Master link assemblies 3-4-I, grade 80

Blueprint



Technical data

| Part code | WLL ton | EWL mm | For chain, 3-4-leg mm | L mm | B mm | D mm | B1 mm | D1 mm | L1 mm | Weight kg |
|-----------|---------|--------|-----------------------|------|------|------|-------|-------|-------|-----------|
| NRLI6 | 2.36 | 189 | 6 | 135 | 75 | 18 | 25 | 14 | 54 | 1.2 |
| NRLI78 | 4.25 | 230 | 7/8 | 160 | 90 | 22 | 34 | 16 | 70 | 2.2 |
| NRLI10 | 6.7 | 265 | 10 | 180 | 100 | 26 | 40 | 18 | 85 | 3.4 |
| NRLI13 | 11.2 | 315 | 13 | 200 | 110 | 32 | 50 | 22 | 115 | 6 |
| NRLI16 | 17 | 400 | 16 | 260 | 140 | 36 | 65 | 26 | 140 | 10 |
| NRLI20 | 26.5 | 500 | 20 | 350 | 190 | 51 | 70 | 32 | 150 | 23.3 |
| NRLI22 | 32 | 520 | 22 | 350 | 190 | 51 | 75 | 36 | 170 | 25.9 |
| NRLI26 | 45 | 570 | 26 | 400 | 200 | 57 | 80 | 40 | 170 | 35.2 |
| NRLI32 | 67 | 817 | 32 | 460 | 250 | 72 | 190 | 49 | 357 | 67.6 |