

Lifting chain, grade 80

Product information



Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

Material: Steel

Marking: According to standard

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black

Standard: EN 818-2

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part code | Chain diameter mm | WLL ton | A mm | B mm | D mm | Weight kg/m |
|------------------|------------------------------|--------------------|-------------|-------------|-----------------|------------------------|
| NK6 | 6 | 1.12 | 18 | 9 | 6 | 0.8 |
| NK7 | 7 | 1.5 | 22 | 10 | 7 | 1.1 |
| NK8 | 8 | 2 | 24 | 12 | 8 | 1.35 |
| NK10 | 10 | 3.15 | 30 | 14 | 10 | 2.15 |
| NK13 | 13 | 5.3 | 39 | 19 | 13 | 3.5 |
| NK16 | 16 | 8 | 48 | 23 | 16 | 5.5 |
| NK20 | 20 | 12.5 | 60 | 25 | 20 | 8.4 |
| NK22 | 22 | 15 | 66 | 28 | 22 | 10.35 |
| NK26 | 26 | 21.2 | 78 | 35 | 26 | 15.8 |
| NK32 | 32 | 31.5 | 96 | 43 | 32 | 23 |
| NK36 | 36 | 40 | 108 | 49 | 36 | 29 |
| NK40 | 40 | 50 | 120 | 54 | 40 | 36 |

Blueprint

