Lifting Solutions Group
Axel Johnson International

Lifting chain, grade 80

Product information

Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

... *Read more*



Material: Steel
Marking: According to standard
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, black
Standard: EN 818-2
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Lifting chain, grade 80

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	B mm	D mm	Weight kg/m
NK6	6	1.12	18	9	6	0.8
NK7	7	1.5	22	10	7	1.1
NK8	8	2	24	12	8	1.35
NK10	10	3.15	30	14	10	2.15
NK13	13	5.3	39	19	13	3.5
NK16	16	8	48	23	16	5.5
NK20	20	12.5	60	25	20	8.4
NK22	22	15	66	28	22	10.35
NK26	26	21.2	78	35	26	15.8
NK32	32	31.5	96	43	32	23
NK36	36	40	108	49	36	29
NK40	40	50	120	54	40	36

© November 2026 - All Rights Reserved