

Latch hook with swivel, grade 80

Product information



Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Latch hook with swivel, grade 80

Blueprint



Technical data

| Part code | WLL ton | EWL mm | For chain Ø mm | K mm | E mm | A mm | B mm | Weight kg |
|-----------|---------|--------|----------------|------|------|------|------|-----------|
| SALKL6 | 1.12 | 138 | 6 | 170 | 22 | 32.5 | 22 | 0.34 |
| SALKL78 | 2 | 167 | 7/8 | 210 | 27 | 35.5 | 26 | 0.85 |
| SALKL10 | 3.15 | 197 | 10 | 247 | 32 | 42 | 34 | 1.54 |
| SALKL13 | 5.3 | 247 | 13 | 302 | 40 | 50 | 38.5 | 3.4 |
| SALKL16 | 8 | 305 | 16 | 382 | 45 | 61 | 55 | 5.36 |
| SALKL20 | 12.5 | 336 | 20 | 418 | 49 | 72 | 61 | 7.4 |
| SALKL22 | 15 | 433 | 22 | 527 | 54 | 95 | 95 | 10.6 |
| SALKL26 | 21.2 | 510 | 26 | 610 | 81 | 122 | 115 | 21.4 |