Lifting Solutions Group
Axel Johnson International

Lift graded turnbuckles with closed body

Product information

Lift graded turnbuckle for professional use. Equipped with locking nuts and fork/fork ends.

... *Read more*



Material: Steel
Marking: CE-mark, WLL | batch | Haklift
Finish: M6/M8 electric galvanized | M10-M52 hot dip galvanized


Safety factor: 5:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lift graded turnbuckles with closed body

Blueprint



Technical data

Part code	WLL ton	Thread	A mm	B mm	C mm	D mm	E mm	G mm	d mm	h mm	L1 mm	L min. mm	L max. mm	Weight kg
VRH06	0.2	M6	19	7	16	14.5	100	12	M5	6.5	54	180	255	0.13
VRH08	0.32	M8	23	9	22	17.2	108	14	M6	8.5	59	210	285	0.25
VRH10	0.5	M10	26	10	21	17.2	150	17	M8	7	79	250	360	0.3
VRH12	0.7	M12	33	13	26	21.3	195	22	M10	8	106	330	480	0.65
VRH16	1.2	M16	42	18	32	27	230	26	M12	8	122	395	580	1.25
VRH19	1.5	M20	50	20	38	34	270	32	M16	12	145	460	680	2.2
VRH22	2.2	M22	44	25	50	34	295	46	M20	12	160	500	720	3.3
VRH25	3.2	M24	51	28	54	42	325	52	M22	12	175	555	800	4.6
VRH32	4.8	M33	62	38	71.5	50	370	60	M27	12	220	700	970	8.5
VRH38	6	M39	79	45	83.5	60.3	400	75	M33	16	230	780	1,060	15
VRH45	8.5	M45	94	50	86	76	400	85	M39	16	235	800	1,050	21
VRH50	11	M52	98	58	97.5	76	400	92	M45	16	240	825	1,050	24

© November 2026 - All Rights Reserved