Lifting Solutions Group
Axel Johnson International

Shackles, SAE - dee model

Product information



Shackles approved for lifting. Dee shackles are suitable for use when two pieces of lifting equipment / an installment are joined together (one-leg systems). Screw pin shackles are easily manipulated. They are typically suitable for non-permanent applications and one-off installations, when there is no tendency for the pin to unscrew and the shackle can be observed under operation.

... *Read more*

Features: RFID-ready
Material: Steel
Marking: According to standard, CE-mark
Temperature range: -20°C - (+)200°C
Finish: Hot dip galvanized
Standard: US. FED. SPEC. RR-C-271F


Safety factor: 6:1

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Shackles, SAE - dee model

Blueprint



Technical data

Part code	WLL ton	Size inch	A mm	B mm	C mm	D mm	F mm	G mm	H mm	I mm	M mm	Weight kg
SAK03SBP	0.33	3/16	10	7	16	5	14	20	31	4	29	0.02
SAK05SBP	0.5	1/4	12	8	23	7	16	25	41	5	35	0.05
SAK07SBP	0.75	5/16	14	10	26	8	19	30	49	6	42	0.08
SAK10SBP	1	3/8	17	11	32	10	23	36	59	7	52	0.13
SAK15SBP	1.5	7/16	19	13	37	11	27	42	68	8	61	0.2
SAK20SBP	2	1/2	21	16	42	13	30	46	77	10	69	0.27
SAK32SBP	3.25	5/8	27	19	51	16	37	59	96	11	85	0.57
SAK47SBP	4.75	3/4	32	23	61	19	46	70	115	13	101	1.2
SAK65SBP	6.5	7/8	37	26	72	23	53	81	135	13	114	1.43
SAK85SBP	8.5	1	43	29	81	25	61	94	151	14	129	2.15
SAK95SBP	9.5	1-1/8	46	32	91	29	69	103	172	16	142	3.06
SAK120SBP	12	1-1/4	52	35	100	32	76	115	191	18	156	4.11
SAK135SBP	13.5	1-3/8	57	38	111	35	84	127	210	19	174	5.28
SAK170SBP	17	1-1/2	61	42	122	38	92	137	230	21	187	7.23
SAK250SBP	25	1-3/4	73	51	146	45	106	162	279	26	231	12.1
SAK350SBP	35	2	83	57	172	51	122	184	312	31	263	19.2
SAK550SBP	55	2-1/2	105	70	203	67	145	238	377	35	330	32.5

© November 2026 - All Rights Reserved