Lifting Solutions Group
Axel Johnson International

Beam clamps

Product information



The beam clamp provides a safe and reliable attachment point for lifting and suspension applications on I-beams. It is mounted directly onto the beam flange, allowing for quick and straightforward installation. Thanks to its adjustable design, the clamp fits a range of I-beam widths and is an ideal solution for suspending hoists, lifting devices, and other lifting equipment in industrial facilities, construction sites, and maintenance applications.

Especially suitable for

- Suspending hoists and lifting devices from I-beams
- Creating temporary and permanent lifting points
- Lifting applications in industrial facilities, warehouses, and construction sites
- Service and maintenance work

Product features

- Suitable for I-beams
- Beam width adjustable using a threaded spindle
- Attaches to the beam without welding or drilling
- Suitable for suspending hoists, lifting devices, and other lifting equipment
- Durable construction for professional use

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Finish: Painted, yellow
Standard: EN 13155


Safety factor: 4:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Beam clamps

Blueprint



Technical data

Part code	WLL ton	Beam width mm	A mm	B mm	C mm	E mm	Weight kg
TARPAL10	1	75-220	75-260	180-360	64	215	3.8
TARPAL20	2	75-220	75-260	180-3360	74	215	4.6
TARPAL30	3	80-320	80-354	235-490	103	260	9
TARPAL50	5	80-320	90-354	235-490	110	260	11
TARPAL100	10	90-320	80-365	320-505	120	260	16

© November 2026 - All Rights Reserved